

## TECHNICAL DATA SHEET



# LUCAS ANTI-GEL COLD WEATHER DIESEL TREATMENT

PRODUCT # 10865, 10866, 10867, 10868

### TEST

### ASTM

### TYPICAL

<b>API Gravity</b>	<b>D-1298</b>	<b>39.81</b>
<b>Specific Gravity @ 60°F</b>	<b>D-1298</b>	<b>.826</b>
<b>Density @ 60°F LBS/US Gal</b>	<b>D-1298</b>	<b>6.879</b>
<b>Viscosity @ 40°C cSt</b>	<b>D-445</b>	<b>2.8</b>
<b>Flash Point, PMCC °F</b>	<b>D-93</b>	<b>&gt;140</b>
<b>Appearance</b>	<b>Visual</b>	<b>Bright &amp; Clear</b>
<b>Color</b>	<b>Visual</b>	<b>Amber</b>
<b>Odor</b>		<b>Petroleum</b>

Lucas Oil Anti-Gel Cold Weather Diesel Treatment is especially designed to prevent cold filter plugging, fuel thickening and gelling in ULSD, diesel and bio-diesel fuels. The product is manufactured with the highest quality components to provide maximum performance. It contains Real water dispersants to effectively remove moisture from the entire fuel system. It does not contain alcohol, will not void OEM warranties and has no harmful effects on diesel particulate filters. Comes in quarts and 64 ounce bottles and is also available in 5 gallon pails and 55 gallon drums depending on the amount of fuel that is being treated. One quart treats 150 gallons of fuel and lowers the cold filter plugging point to -10°F. For temperatures below -10°F add a second bottle with protection down to -40°F. One 64 ounce bottle treats 300 gallons of fuel and lowers the cold filter plugging point to -10°F. For temperatures below -10°F add a second bottle with protection down to -40°F. Use 64 ounce ratio for 5 gallon pails and 55 gallon drums.

For increased fuel mileage, fewer exhaust emissions and extended engine life use LUCAS UPPER CYLINDER LUBRICANT at every fill up (Part # 10003, 10013).